

PED 200 + PED/GL

Fire rated



PED 200 + PED/GL

Characteristics of PED 200

- Set of PED composed of Modular Cross Bar and kit for 2/3 lateral locking points
- Modular cross bar type
- For Fire and Smoke applications
- High durability 200,000 cycles
- One central locking point
- For one or double leaf door up to 200 kg
- For all types of the door
- For doors up to 1200 mm width in standard
- For doors up to 1400 mm width in option
- Steel pulman latch in standard
- Dead latch in standard
- Steel or zinc alloy swing latch
- Zinc alloy or s/steel cover 38 mm length
- Steel or s/steel bar 1075 mm long
- Bar to be cut
- 97 mm projection
- HO function in option
- Micro switch version in option

EN 1125 certification:

3 7 6 0/B* 1 3 2 2 A A

Characteristics of PED/GL

- Set of rods, rod covers and lateral latches
- To fit modular cross bar
- For 2 lateral locking points installation
- For one or double leaf door
- For doors up to 2350 mm high in standard
- For doors up to 3200 mm high in option
- Steel pulman latches
- Dead latches in standard

Accessories

- Outside trims Modular series
- Half cylinder (MKS possible)
- Various strikers
- Glass door installation kit
- Rod extension for doors up to 3200 mm

Finishes

- | | | |
|-------------------|-------------------|-------------------|
| • Latches covers: | • Bars: | • Rod covers |
| • Black RAL 9005 | • Red RAL 3000 | • Black RAL 9005 |
| • Silver RAL 9006 | • Silver RAL 9006 | • Silver RAL 9006 |
| • S/Steel effect | • S/Steel | • S/Steel effect |
| • S/Steel | | |

Specification

Outside device	Blind plate	Modular lever handle
No outside opening	•	
Free passing door		•
Cylinder looking - knob / lever handle opening		•

Ordering numbers

Ordering number	Accessories	Material	Description
PED 200/-/GG	MNAT101M02SGGAA	cross bar	central locking point PED with steel latch and dead latch, 1200 mm wide door, grey support and bar
PED 200/-/NR	MNAT101M02SNRAA	cross bar	central locking point PED with steel latch and dead latch, 1200 mm wide door, black support and red bar
PED 200/-/SI	MNAT101M02SSIAAA	cross bar	central locking point PED with steel latch and dead latch, 1200 mm wide door, s/steel effect support and s/steel bar
PED 200/-/II	MNAT101M02SIIAAA	cross bar	central locking point PED with steel latch and dead latch, 1200 mm wide door, s/steel support and bar
PED 200/HO/GG	MNAT111M02SGGAA	cross bar	central locking point PED with steel latch and dead latch, 1200 mm wide door, grey support and bar - HO function
PED 200/HO/NR	MNAT111M02SNRAA	cross bar	central locking point PED with steel latch and dead latch, 1200 mm wide door, black support and red bar - HO function
PED 200/HO/SI	MNAT111M02SSIAAA	cross bar	central locking point PED with steel latch and dead latch, 1200 mm wide door, s/steel effect support and s/steel bar - HO function
PED 200/HO/II	MNAT111M02SIIAAA	cross bar	central locking point PED with steel latch and dead latch, 1200 mm wide door, s/steel support and bar - HO function
PED/GL/G	KITMNC1S3SLFG	lateral KIT	Modular KIT for two lateral locking points and rod cover PED with steel latch grey support and vertical rod cover
PED/GL/N	KITMNC1S3SLFN	lateral KIT	Modular KIT for two lateral locking points and rod cover PED with steel latch black support and vertical rod cover
PED/GL/S	KITMNC1S3SLFS	lateral KIT	Modular KIT for two lateral locking points and rod cover PED with steel latch satin support and vertical rod cover

